

---

# **Genomedata Documentation**

*Release 1.4.1*

**Michael M. Hoffman**

**Jun 08, 2018**



# CONTENTS

|                                       |           |
|---------------------------------------|-----------|
| <b>1 Genomedata 1.4 documentation</b> | <b>3</b>  |
| 1.1 Installation . . . . .            | 3         |
| 1.2 Overview . . . . .                | 4         |
| 1.3 Implementation . . . . .          | 5         |
| 1.4 Creation . . . . .                | 5         |
| 1.5 Genomedata usage . . . . .        | 7         |
| 1.6 Tips and tricks . . . . .         | 14        |
| 1.7 Technical matters . . . . .       | 14        |
| 1.8 Bugs . . . . .                    | 15        |
| 1.9 Support . . . . .                 | 15        |
| <b>2 Indices and tables</b>           | <b>17</b> |
| <b>Python Module Index</b>            | <b>19</b> |
| <b>Index</b>                          | <b>21</b> |



Contents:



## GENOMEDATA 1.4 DOCUMENTATION

**Website** <http://pmgenomics.ca/hoffmanlab/proj/genomedata/>

**Author** Michael M. Hoffman <michael dot hoffman at utoronto dot ca>

**Organization** Princess Margaret Cancer Centre

**Address** Toronto Medical Discovery Tower 11-311, 101 College St, M5G 1L7, Toronto, Ontario, Canada

**Copyright** 2009-2014 Michael M. Hoffman

For a broad overview, see the paper:

Hoffman MM, Buske OJ, Noble WS. (2010). [The Genomedata format for storing large-scale functional genomics data](#). *Bioinformatics*, **26**(11):1458-1459; doi:10.1093/bioinformatics/btq164

Please cite this paper if you use Genomedata.

### 1.1 Installation

Python (2.6 or 2.7) and the HDF5 libraries are required before you can install Genomedata.

#### 1.1.1 Installing HDF5

Ubuntu/Debian:

```
sudo apt-get install libhdf5-serial-dev hdf5-tools
```

CentOS/RHEL/Fedora:

```
sudo yum -y install hdf5 hdf5-devel
```

OpenSUSE:

```
sudo zypper in hdf5 hdf5-devel libhdf5
```

If HDF5 has been installed from source, set the HDF5\_DIR environment variable to the directory where it was installed.

#### 1.1.2 Installing Numpy

With Python 2.6 or 2.7 installed:

```
pip install numpy
```

### 1.1.3 Installing Genomedata

With Python 2.6 or 2.7 installed:

```
pip install genomedata
```

**Note:** The latest version of genomedata may not will not install with older versions of pip (< 6.0) due to some of the dependencies requiring a newer version. You can update your pip using the command:

```
pip install --upgrade pip
```

**Note:** Genomedata is only supported on 64 bit systems.

**Note:** The following are prerequisites:

- **Linux/Unix** This software has been tested on Linux and Mac OS X systems. We would love to add support for other systems in the future and will gladly accept any contributions toward this end.
- Zlib

**Note:** For questions, comments, or troubleshooting, please refer to the [support](#) section.

## 1.2 Overview

Genomedata provides a way to store and access large-scale functional genomics data in a format which is both space-efficient and allows efficient random-access. Genomedata archives are currently write-once, although we are working to fix this.

Under the surface, Genomedata is *implemented* as one or more HDF5 files, but Genomedata provides a transparent interface to interact with your underlying data without having to worry about the mess of repeatedly parsing large data files or having to keep them in memory for random access.

The Genomedata hierarchy:

**Each Genome contains many Chromosomes**

**Each Chromosome contains many Supercontigs**

**Each Supercontig contains one continuous data set** Each continuous data set is a numpy.array of floating point numbers with a column for each data track and a row for each base in the data set.

**Why have Supercontigs?** Genomic data seldom covers the entire genome but instead tends to be defined in large but scattered regions. In order to avoid storing the undefined data between the regions, chromosomes are divided into separate supercontigs when regions of defined data are far enough apart. They also serve as a convenient chunk since they can usually fit entirely in memory.

## 1.3 Implementation

Genomedata archives are implemented as one or more HDF5 files. The *API* handles both single-file and directory archives transparently, but the implementation options exist for several performance reasons.

### Use a directory with few chromosomes/scaffolds:

- Parallel load/access
- Smaller file sizes

### Use a single file with many chromosomes/scaffolds:

- More efficient access with many chromosomes/scaffolds
- Easier archive distribution

Implementing the archive as a directory makes it easier to parallelize access to the data. In particular, it makes it easy to create the archives in parallel with one chromosome on each machine. It also reduces the likelihood of running into the 2 GB file limit applicable to older applications and older versions of 32-bit UNIX. We are currently using an 81-track Genomedata archive for our research which has a total size of 18 GB, but the largest single file (chr1) is only 1.6 GB.

A directory-based Genomedata archive is not ideal for all circumstances, however, such as when working with genomes with many chromosomes, contigs, or scaffolds. In these situations, a single file implementation would be much more efficient. Additionally, having the archive as a single file allows the archive to be distributed much more easily (without tar/zip/etc).

---

**Note:** The default behavior is to implement the Genomedata archive as a directory if there are fewer than 100 sequences being loaded and as a single file otherwise.

---

New in version 1.1: Single-file-based Genomedata archives

## 1.4 Creation

A Genomedata archive contains sequence and may also contain numerical data associated with that sequence. You can easily load sequence and numerical data into a Genomedata archive with the *genomedata-load* command (see command details additional details):

```
genomedata-load [-t trackname=signalfile]... [-s sequencefile]... GENOMEDATAFILE
```

This command is a user-friendly shortcut to the typical workflow. The underlying commands are still installed and may be used if more fine-grained control is required (for instance, parallel data loading or adding additional tracks later). The commands and required ordering are:

1. *genomedata-load-seq*
2. *genomedata-open-data*
3. *genomedata-load-data*
4. *genomedata-close-data*

Entire data tracks can later be replaced with the following pipeline:

1. *genomedata-erase-data*
2. *genomedata-load-data*

### 3. *genomedata-close-data*

New in version 1.1: The ability to replace data tracks.

Additional data tracks can be added to an existing archive with the following pipeline:

1. *genomedata-open-data*
2. *genomedata-load-data*
3. *genomedata-close-data*

New in version 1.2: The ability to add data tracks.

As of the current version, Genomedata archives must include the underlying genomic sequence and can only be created with *genomedata-load-seq*. A Genomedata archive can be created without any tracks, however, using the following pipeline:

1. *genomedata-load-seq*
2. *genomedata-close-data*

New in version 1.2: The ability to create an archive without any data tracks.

Additionally, you may remove portions of data from tracks by hardmasking the specified data tracks. This can be done anytime after loading in data and unless specified otherwise will automatically close the archive as well. A track can be loaded and filtered with the following pipeline:

1. *genomedata-open-data*
2. *genomedata-load-data*
3. *genomedata-hardmask*

New in version 1.4: The ability to hardmask tracks.

---

**Note:** A call to **h5repack** after *genomedata-close-data* may be used to transparently compress the data.

---

## 1.4.1 Example

The following is a brief example for creating a Genomedata archive from sequence and signal files.

Given the following two sequence files:

1. A text file, *chr1.fa*:

```
>chr1
taaccctaaccctaaccctaaccctaaccctaaccctaaccctaacccta
accctaaccctaaccctaaccctaaccct
```

2. A compressed text file, *chrY.fa.gz*:

```
>chrY
ctaaccctaaccctaaccctaaccctaaccctaaccctCTGaaagtggac
```

and the following two signal files:

1. *signal\_low.wigFix*:

```
fixedStep chrom=chr1 start=5 step=1
0.372
-2.540
0.371
-2.611
0.372
-2.320
```

## 2. *signal\_high.bed.gz*:

```
chrY 0 12 4.67
chrY 20 23 9.24
chr1 1 3 2.71
chr1 3 6 1.61
chr1 6 24 3.14
```

A Genomedata archive (`genomedata.test`) could then be created with the following command:

```
genomedata-load -s chr1.fa -s chrY.fa.gz -t low=signal_low.wigFix \
-t high=signal_high.bed.gz genomedata.test
```

or the following pipeline:

```
genomedata-load-seq genomedata.test chr1.fa chrY.fa.gz
genomedata-open-data genomedata.test low high
genomedata-load-data genomedata.test low < signal_low.wigFix
zcat signal_high.bed.gz | genomedata-load-data genomedata.test high
genomedata-close-data genomedata.test
```

**Note:** `chr1.fa` and `chrY.fa.gz` could also be combined into a single sequence file with two sequences.

**Note:** If using a glob syntax for your sequence files, remember to put the glob filename in quotes to avoid having your shell expand the glob before it `genomedata-load` uses it (e.g. `-s "chr*.agp.gz"`)

**Warning:** It is important that the sequence names (*chrY*, *chr1*) in the signal files match the sequence identifiers in the sequence files exactly.

## 1.5 Genomedata usage

### 1.5.1 Python interface

The data in Genomedata is accessed through the hierarchy described in *Overview*. A full *Python API* is also available.

**Note:** The Python API expects that a genomedata archive has already been created. This can be done manually via the *genomedata-load* command. Alternatively, this can be done programmatically using `:_load_seq:load_seq`.

To appreciate the full benefit of Genomedata, it is most easily used as a contextmanager:

```
from genomedata import Genome
[...]
gdfilename = "/path/to/genomedata/archive"
with Genome(gdfilename) as genome:
    [...]
```

---

**Note:** If `Genome` is used as a context manager, it will clean up any opened Chromosomes automatically. If not, the `Genome` object (and all opened chromosomes) should be closed manually with a call to `Genome.close()`.

---

### 1.5.2 Basic usage

Genomedata is designed to make it easy to get to the data you want.

Here are a few examples:

**Get arbitrary sequence** (10-bp sequence starting at chr2:1423):

```
>>> chromosome = genome["chr2"]
>>> seq = chromosome.seq[1423:1433]
>>> seq
array([116,  99,  99,  99,  99, 103, 103, 103, 103, 103], dtype=uint8)
>>> seq.tostring()
'tccccggggg'
```

**Get arbitrary data** (data from first 3 tracks for region chr8:999-1000):

```
>>> chromosome = genome["chr8"]
>>> chromosome[999:1001, 0:3] # Note the half-open, zero-based indexing
array([[ NaN,  NaN,  NaN],
       [ 3. ,  5.5,  3.5]], dtype=float32)
```

**Get data for a specific track** (specified data in first 5-bp of chr1):

```
>>> chromosome = genome["chr1"]
>>> data = chromosome[0:5, "sample_track"]
>>> data
array([ 47.,  NaN,  NaN,  NaN,  NaN], dtype=float32)
```

*Only specified data:*

```
>>> from numpy import isfinite
>>> data[isfinite(data)]
array([ 47.], dtype=float32)
```

---

**Note:** Specify a slice for the track to keep the data in column form:

```
>>> col_index = chromosome.index_continuous("sample_track")
>>> data = chromosome[0:5, col_index:col_index+1]
```

---

### Command-line interface

Genomedata archives can be created and loaded from the command line with the `genomedata-load` command.

### 1.5.3 genomedata-load

This is a convenience script that will do everything necessary to create a Genomedata archive. This script takes as input:

- assembly files in either **FASTA** (.fa or .fa.gz) format (where the sequence identifiers are the names of the chromosomes/scaffolds to create), or assembly files in AGP format (when used with `--assembly`). This is **mandatory**, despite having an option interface.
- **trackname, datafile pairs (specified as trackname=datafile), where:**
  - trackname is a string identifier (e.g. broad.h3k27me3)
  - datafile contains signal data for this data track in one of the following formats: **WIG**, **BED3+1**, **bed-Graph**, or a gzip'd form of any of the preceding
  - the chromosomes/scaffolds referred to in the datafile **MUST** be identical to those found in the sequence files
- the name of the Genomedata archive to create

See the *full example* for more details.

Command-line usage information:

```
usage: genomedata-load [-h] [-v] [--verbose] -s SEQUENCE -t NAME=FILE
                        [--assembly | --sizes] [-f | -d]
                        GENOMEDATAFILE

Create Genomedata archive named GENOMEDATAFILE by loading
specified track data and sequences. If GENOMEDATAFILE
already exists, it will be overwritten.
--track and --sequence may be repeated to specify
multiple trackname=trackfile pairings and sequence files,
respectively.

Example: genomedata-load -t high=signal.high.wig -t low=signal.low.bed.gz -s chrX.fa
↪ -s chrY.fa.gz gdarchive

positional arguments:
  GENOMEDATAFILE      genomedata archive

optional arguments:
  -h, --help          show this help message and exit
  -v, --version       show program's version number and exit

Flags:
  --verbose          Print status updates and diagnostic messages

Input data:
  -s SEQUENCE, --sequence SEQUENCE
                        Add the sequence data in the specified file or files
                        (may use UNIX glob wildcard syntax)
  -t NAME=FILE, --track NAME=FILE
                        Add data from FILE as the track NAME, such as: -t
                        signal=signal.wig
  -m MASKFILE, --maskfile MASKFILE
                        A BED file containing regions to mask out from tracks
                        before loading
  --assembly          sequence files contain assembly (AGP) files instead of
```

(continues on next page)

(continued from previous page)

|                      |   |
|----------------------|---|
|                      | sequence  |
| --sizes              | sequence files contain <code>list</code> of sizes instead of sequence   |
| Implementation:      |   |
| -f, --file-mode      | If specified, the Genomedata archive will be implemented <b>as</b> a single file, <b>with</b> a separate h5 group <b>for</b> each Chromosome. This <b>is</b> recommended <b>if</b> there are a large number of Chromosomes. The default behavior <b>is</b> to use a single file <b>if</b> there are at least 100 Chromosomes being added. |
| -d, --directory-mode | If specified, the Genomedata archive will be implemented <b>as</b> a directory, <b>with</b> a separate file <b>for</b> each Chromosome. This <b>is</b> recommended <b>if</b> there are a small number of Chromosomes. The default behavior <b>is</b> to use a directory <b>if</b> there are fewer than 100 Chromosomes being added.       |

Alternately, as described in [Overview](#), the underlying Python and C load scripts are also accessible for more finely-grained control. This can be especially useful for parallelizing Genomedata loading over a cluster.

You can use wildcards when specifying sequence files, such as in `genomedata-load-seq -s 'chr*.fa'`. You must be sure to quote the wildcards so that they are not expanded by your shell. For most shells, this means using single quotes ('chr\*.fa') instead of double quotes ("chr\*.fa").

If you aren't going to use the sequence later on, loading the assembly from an AGP file will be faster and take less memory during loading, and disk space afterward.

## 1.5.4 genomedata-load-seq

This command adds the provided sequence files to the specified Genomedata, archive creating it if it does not already exist. Sequence files should be in FASTA (.fa or .fa.gz) format. Gaps of  $\geq 100,000$  base pairs in the reference sequence, are used to divide the sequence into supercontigs. The FASTA definition line will be used as the name for the chromosomes/scaffolds created within the Genomedata archive and must be consistent between these sequence files and the data loaded later with `genomedata-load-data`. See [this example](#) for details.

|   |   |
|---|---|
| usage: genomedata-load-seq [-h] [-v] [-a] [-s] [-f] [-d] [--verbose]  |   |
| GENOMEDATAFILE seqfiles [seqfiles ...]  |   |
| Start a Genomedata archive at GENOMEDATAFILE <b>with</b> the provided sequences. SEQFILES should be <b>in</b> fasta <b>format</b> , <b>and</b> a separate Chromosome will be created <b>for</b> each definition line. |   |
| positional arguments:   |   |
| gdarchive   | genomedata archive  |
| seqfiles  | sequences <b>in</b> FASTA <b>format</b>   |
| optional arguments:   |   |
| -h, --help  | show this help message <b>and</b> exit  |
| -v, --version   | show program's <b>version number</b> and exit   |
| -a, --assembly  | SEQFILE contains assembly (AGP) files instead of sequence   |
| -s, --sizes   | SEQFILE contains <code>list</code> of sizes instead of sequence   |
| -f, --file-mode   | If specified, the Genomedata archive will be implemented <b>as</b> a single file, <b>with</b> a separate h5 group |

(continues on next page)

(continued from previous page)

```

for each Chromosome. This is recommended if there are
a large number of Chromosomes. The default behavior is
to use a single file if there are at least 100
Chromosomes being added.
-d, --directory-mode  If specified, the Genomdata archive will be
implemented as a directory, with a separate file for
each Chromosome. This is recommended if there are a
small number of Chromosomes. The default behavior is
to use a directory if there are fewer than 100
Chromosomes being added.
--verbose             Print status updates and diagnostic messages

```

### 1.5.5 genomdata-open-data

This command opens the specified tracks in the Genomdata archive, allowing data for those tracks to be loaded with *genomdata-load-data*.

```

usage: genomdata-open-data [-h] [-v] --trackname TRACKNAME [TRACKNAME ...]
                             [--verbose]
                             gdarchive

```

Open one **or** more tracks **in** the specified Genomdata archive.

positional arguments:

```

  gdarchive          genomdata archive

```

optional arguments:

```

-h, --help          show this help message and exit
-v, --version       show program's version number and exit
--trackname TRACKNAME [TRACKNAME ...]
                    tracknames to open
--verbose           Print status updates and diagnostic messages

```

### 1.5.6 genomdata-hardmask

This command permanently and irreversibly masks out regions from tracks in the Genomdata archive. Due to slow performance, it is not recommended for masking large genome-wide datasets. In the case of very large datasets, it is recommended you mask or filter your data first, then load the masked data with *genomdata-load-data*.

```

usage: genomdata-hardmask [-h] [-v] [-t TRACKNAME [TRACKNAME ...]]
                             [--hardmask OPERATOR] [--no-close] [--dry-run]
                             [--verbose]
                             maskfile gdarchive

```

Permanently mask TRACKNAME(s) **from a** genomdata archive **with** MASKFILE using an optional **filter** operator.

positional arguments:

```

  maskfile          input mask file
  gdarchive          genomdata archive

```

optional arguments:

```

-h, --help          show this help message and exit

```

(continues on next page)

(continued from previous page)

```

-v, --version          show program's version number and exit
-t TRACKNAME [TRACKNAME ...], --trackname TRACKNAME [TRACKNAME ...]
                        Track(s) to be filtered (default: all)
--hardmask OPERATOR   Specify a comparison operation on a value to mask out
                        (e.g. "<0.5" will mask all values less than 0.5). See
                        the bash comparison operators for the two letter
                        operations (default: all values masked)
--no-close            Do not close the genomedata archive after masking
--dry-run            Do not perform any masking. Useful with verbosity set
                        to see what regions would be filtered
--verbose            Print status and diagnostic messages

```

## 1.5.7 genomedata-load-data

This command loads data from stdin into Genomedata under the given trackname. The input data must be in one of these supported datatypes: [WIG](#), [BED3+1](#), [bedGraph](#). The chromosome/scaffold references in these files must match the sequence identifiers in the sequence files loaded with [genomedata-load-seq](#). See [this example](#) for details. A `chunk-size` can be specified to control the size of hdf5 chunks (the smallest data read size, like a page size). Larger values of `chunk-size` can increase the level of compression, but they also increase the minimum amount of data that must be read to access a single value.

BED3+1 format is interpreted the same ways as bedGraph, except that the track definition line is not required.

```
Usage: genomedata-load-data [OPTION...] GENOMEDATAFILE TRACKNAME
```

Loads data into Genomedata format

Takes track data in on stdin

```

-c, --chunk-size=NROWS  Chunk hdf5 data into blocks of NROWS. A higher
                        value increases compression but slows random
                        access. Must always be smaller than the max size
                        for a dataset. [default: 10000]
-?, --help              Give this help list
--usage                 Give a short usage message
-V, --version           Print program version

```

Mandatory or optional arguments to long options are also mandatory or optional for any corresponding short options.

## 1.5.8 genomedata-close-data

Closes the specified Genomedata archive.

```
usage: genomedata-close-data [-h] [-v] [--verbose] gdarchive
```

Compute summary statistics **for** data **in** Genomedata archive **and** ready **for** accessing.

positional arguments:

```
gdarchive    genomedata archive
```

optional arguments:

```

-h, --help          show this help message and exit
-v, --version       show program's version number and exit
--verbose           Print status updates and diagnostic messages

```

## 1.5.9 genomedata-erase-data

Erases all data associated with the specified tracks, allowing the data to then be replaced. The pipeline for replacing a data track is:

1. *genomedata-erase-data*
2. *genomedata-load-data*
3. *genomedata-close-data*

```
usage: genomedata-erase-data [-h] [-v] --trackname TRACKNAME [TRACKNAME ...]
                               [--verbose]
                               gdarchive
```

Erase the specified tracks **from the** Genomedata archive **in** such a way that the track data can be replaced (via *genomedata-load-data*).

positional arguments:

```
gdarchive          genomedata archive
```

optional arguments:

```
-h, --help          show this help message and exit
-v, --version       show program's version number and exit
--trackname TRACKNAME [TRACKNAME ...]
                    tracknames to erase
--verbose           Print status updates and diagnostic messages
```

## 1.5.10 genomedata-info

This command displays information about a genomedata archive. Running the following command:

```
genomedata-info tracknames_continuous genomedata
```

displays the list of continuous tracks. Running:

```
genomedata-info contigs genomedata
```

displays the list of contigs in BED format (0-based, half-open indexing).

This command generates a tab-delimited file containing chromosome name and sizes, suitable for use as a UCSC “chrom sizes” file:

```
genomedata-info sizes genomedata
```

```
usage: genomedata-info [-h] [-v]
                        {tracknames,tracknames_continuous,contigs,sizes}
                        gdarchive
```

Print information about a genomedata archive.

positional arguments:

```
{tracknames,tracknames_continuous,contigs,sizes}
                    available commands
gdarchive          genomedata archive
```

optional arguments:

(continues on next page)

(continued from previous page)

```
-h, --help          show this help message and exit
-v, --version       show program's version number and exit
```

## 1.5.11 genomedata-query

Prints data from a genomedata archive, for the track TRACKNAME, on CHROM, in the region BEGIN-END (0-based, half-open indexing). Intended as a convenience function only; this is much slower than the Python interface, so it should not be used for large regions.

```
usage: genomedata-query [-h] [-v] gdarchive trackname chrom begin end

print data from genomedata archive in specified trackname and coordinates

positional arguments:
  gdarchive      genomedata archive
  trackname     track name
  chrom         chromosome name
  begin         chromosome start
  end           chromosome end

optional arguments:
  -h, --help          show this help message and exit
  -v, --version       show program's version number and exit
```

## Python API

The Genomedata package is designed to be used from a variety of scripting languages, but currently only exports the following Python API.

## 1.6 Tips and tricks

If you find yourself creating many Genomedata archives on the same genome, it might be useful to save a copy of an archive after you load sequence, but before you load any data. Obviously, you can only do this if you use the fine-grained workflow of *genomedata-load-seq*, *genomedata-open-data*, *genomedata-load-data*, and *genomedata-close-data*.

## 1.7 Technical matters

### 1.7.1 Chunking and chunk cache overhead

Genomedata uses an HDF5 data store. The data is stored in **chunks**. The chunk size is 10,000 bp and one data track of 32-bit single-precision floats, which makes the chunk 40 kB. Each chunk is gzip compressed so on disk it will be smaller. To read a single position you have to read its entire chunk off of the disk and then decompress it. There is a tradeoff here between latency and throughput. Larger chunk sizes mean more latency but better throughput and better compression.

The only disk storage overhead is that compression is slightly less efficient than compressing the whole binary data file when you break it into chunks. This is far outweighed by the efficient random access capability. If you have different

needs, then it should be possible to change the chunk shape (`genomedata.CONTINUOUS_CHUNK_SHAPE`) or compression method (`genomedata._util.FILTERS_GZIP`).

The memory overhead is dominated by the chunk cache defined by PyTables. On the version of PyTables we use, this is 2 MiB. You can change this by setting `tables.parameters.CHUNK_CACHE_SIZE`.

## 1.8 Bugs

There is currently an interaction between Genomedata and PyTables that can result in the emission of Performance-Warnings when a Genomedata file is opened. These can be ignored. We would like to fix these at some point.

## 1.9 Support

To stay informed of **new releases**, subscribe to the moderated `genomedata-announce` mailing list (mail volume very low):

<https://listserv.utoronto.ca/cgi-bin/wa?A0=genomedata-announce-l>

For **discussion and questions** about the use of the Genomedata system, there is a `genomedata-users` mailing list:

<https://mailman1.u.washington.edu/mailman/listinfo/genomedata-users>

For issues related to the use of Genomedata on **Mac OS X**, please use the above mailing list or contact Jay Hesselberth <jay dot hesselberth at ucdenver dot edu>.

If you want to **report a bug or request a feature**, please do so using our issue tracker:

<https://bitbucket.org/hoffmanlab/genomedata/issues>

For other support with Genomedata, or to provide feedback, please write contact the authors directly. We are interested in all comments regarding the package and the ease of use of installation and documentation.



## INDICES AND TABLES

- genindex
- modindex
- search



## PYTHON MODULE INDEX

### g

genomedata, 14



## G

genomedata (module), 14